

# Acoustic panel P series

Modular solution for the acoustic treatment



## Use

Product designed for the acoustic treatment in medical environments such as audiology centres, hearing aids shops and for those who need a professional and technical room. Acoustic panels P series are in anthracite grey polyurethane with high thickness and milled to grant excellent values of acoustic absorption at medium and high frequencies (500-2000 Hz.). Their application significantly reduces the reverberation and it is ideal to perform audiology tests, including Free Field, in a suitable environment. Acoustic panels can be also applied inside our soundproof booth PRO45S.

## Performance

P series panels shall be applied on the 50% of the surface to treat (walls and ceilings) in order to obtain an optimal sound absorption. Thanks to the special 45° flared edges you can have a continuity between walls, ceilings and corners ensuring the homogeneity of the project and creating an almost anechoic environment. Available sets for rooms (calculated according to the rooms dimensions).



## Application

The laying of panels is very easy: simply draw a cross and a perimeter on the back of the panels using the glue provided and lay them against the wall / ceiling by pushing for less than a minute. It is recommended to design a laying pattern before starting the application. Panels are provided with Velcro strips for the installation inside PRO45S booth.



All our products offer the best of Italian design

# Acoustic panel P series

Modular solution for the acoustic treatment



## Sound absorption coefficient (average $\alpha_w$ 0.95)

Hertz	250	500	1000	2000	4000
$\alpha_s$	0.30	0.62	0.85	0.99	0.95

## Available items (can be ordered separately)

Code	Image	Description	Content
AP.4808P		Panel dimensions cm 48 x 48 x 8 in milled anthracite grey polyurethane	6 panels per box
AP.GLUES		Tube of special waterbased glue	Tube for application of 6 panels AP.4808P

## Available sets for rooms (calculated according to the rooms dimensions)

Room dimension (walkable sq.m)	Kit composition (boxes nr.)	Room dimension (walkable sq.m)	Kit composition (boxes nr.)
4 sq.m	N.5 - AP.4808P N.8 - AP.GLUES	12 sq.m	N.12 - AP.4808P N.16 - AP.GLUES
6 sq.m	N.7 - AP.4808P N.10 - AP.GLUES	16 sq.m	N.18 - AP.4808P N.25 - AP.GLUES
9 sq.m	N.9 - AP.4808P N.13 - AP.GLUES	20 sq.m	N.22 - AP.4808P N.30 - AP.GLUES

**Notes** Panels AP.4808P are composed by anthracite grey polyurethane with high thickness and special milled.  
Panels AP.4808P have an higher sound-absorbing feature, ideal for acoustic correction.  
They should not be used as alternative of the silent cabin since AP.4808P panels are not designed for noise reduction.

