Free Field Configuration





- The smartest configuration for your soundproof booth
- Designed to perform Free Field test in a wide selection of booths
- Includes a package of optionals that enhance the booth





Technical specification

Free Field Configuration is a full set up of optionals which help to connect the soundproof booth with the equipments required to perform the Free Field test. Designed for different lines of booths and several dimensions. This package includes important elements that enhance the booth and provide added value to the product. In the below table we present different solutions for frontal free field test (speakers at 45°), diagonal free field test (90°), lateral free field test (180°) with patient head at 1 mt. distance from the speakers.

Air Ventilation System

Since Free Field test requires more time to be performed, the air exchange inside the cabin is guaranteed by a silent forced ventilation system mounted on top of the booth. On PRO45S* line air ventilation is already included.

Ramps for easy access

No hurdles to enter the booth. Ramps allow easy access to wheelchairs too.

Internal Power socket(s)

Power sockets connecting speakers and instruments.

External Folding table

Space-saver solution as support for external instruments.

Supports for speakers

Predisposition for speakers inside the booth, provided in DIY kit for self and customized installation (only for PRO 30 and PRO 35F line).

Availability and applications

	DIMEN	OPTIONALS					
	External cm (LxWxH)	Internal cm (LxWxH)	Air Ventilation	Ramps for easy access	Power socket	Folding table	Speakers Supports
PRO30 LINE							
P30MAXI	132 x 132 x 242	117 x 117 x 201	1	1	1	1	2
P302X1	211 x 107 x 242	196 x 92 x 201	1	1	1	1	2
P302X2	211 x 211 x 242	196 x 196 x 201	1	1	2	1	4
P303X2	314 x 211 x 242	299 x 196 x 201	2	1	3	1	4
P303X2	314 x 211 x 242	299 x 196 x 201	2	1	3	1	4
P303X3	314 x 314 x 242	299 x 299 x 201	2	1	4	1	6
PRO35F LINE							
P35FMAXI	132 x 132 x 242	117 x 117 x 201	1	1	1	1	2
P35F1.3X2	132 x 211 x 242	117 x 196 x 201	1	1	1	1	2
P35F2X1	211 x 107 x 242	196 x 92 x 201	1	1	1	1	2
P35F1.3X2.6	132 x 260 x 242	117 x 245 x 201	1	1	2	1	4
P35F2X2	211 x 211 x 242	196 x 196 x 201	1	1	2	1	4
P35F2X2.6	211 x 260 x 242	196 x 245 x 201	2	1	3	1	4
P35F3X2	314 x 211 x 242	299 x 196 x 201	2	1	3	1	4
P35F3X3	314 x 314 x 242	299 x 299 x 201	2	1	4	1	6
PRO45S LINE							
P45SMAXI	132 x 132 x 244	116 x 116 x 201	1*	1	1	1	•
P45S2X1	216 x 114 x 244	200 x 98 x 201	1*	1	1	1	•
P45S2X2	216 x 216 x 244	200 x 200 x 201	1*	1	2	1	•
P45S3X2	318 x 216 x 244	302 x 200 x 201	2*	1	3	1	•
P45S3X3	318 x 318 x 244	302 x 302 x 201	2*	1	4	1	•

= Speakers can be placed anywhere inside PRO45S line and there is no need to arrange any support.
P30MAXI, P35FMAXI, P45SMAXI are the smallest available options for Free Field configuration pack with speakers at 45°





